

DX850

LABEL DISPENSER



NEW!

Primera's new DX850 Label Dispenser helps you quickly and easily peel and present labels from rolls.

The built-in precision micro-switch detects when a label has been removed. Then, the next label is quickly and automatically fed forward, ready to remove. You'll be able to apply labels much more quickly than ever before. A built-in LED display counts up or down, indicating how many labels you've applied or how many you have left.



BRISBANE
6 Colebard St West
Acacia Ridge, QLD, 4108
Ph: 07 3710 7000
Fax: 07 3710 7010

SYDNEY
Ground Floor 30 Cowper St
Parramatta, NSW, 2150
Ph: +61 2 8011 3713
Mob: 0449 904 177

MELBOURNE
Level 5, 11 Queens Rd,
St Kilda, VIC, 3182
Ph: +61 3 9016 9761
Mob: 0417 631 441

All Mail & International
PO BOX 363
Archerfield BC, QLD, 4108
Int Ph: +61 7 3710 7000
Int Fax: +61 7 3710 7010



Fast and Easy Label Dispensing

The DX850 Label Dispenser automatically peels and presents self-adhesive labels one at a time. It replaces manual label peeling, making your production lines faster and more efficient.

DX850 is robust and reliable, made in the USA of heavy-duty sheet metal and machined steel. It is also one of the few label dispensers available with UL, UL-C, CE listings, FCC approval and RoHS compliance.

Features

- » Easy to use – no screws or clamps to adjust
- » Full range of motion – left or right justification of labels is not necessary; operator can adjust to the most convenient position
- » High-precision, reliable micro-switch activation – nothing to clean or get dirty; works with virtually any label including clear labels
- » LED display – with built-in up/down counter for labels dispensed
- » Universal Power Supply – simply change line cord for use in any country



Specifications

| | |
|-------------------------------|---|
| Supply roll diameter: | Up to 8" (203mm) |
| Media liner width: | 1.00" to 8.38" (25.4mm to 213.0mm) |
| Label height/length: | 0.75" to 24.00" (19.1mm to 609.6mm) |
| Supply roll core: | 2" to 3" (51.8mm to 76.2mm) |
| Label width: | 0.75" to 8.25" (19.1mm to 209.6mm) |
| Electrical rating: | 12 VDC, 5.0 A |
| Power requirements: | 100-240VAC, 50/60 Hz, 60 watts |
| Feed speed: | 4 in/sec. in Default Mode. 2 in/sec in Half-speed Mode for 6-8" wide labels |
| Agency certifications: | UL, UL-C, CE, FCC Class B |
| Weight: | 11.5 lbs (5.2 kg) |
| Dimensions: | 13.44" W x 8.75" H x 11.25" D (341 mm W x 222 mm H x 2876 mm D) |